


Road Pavements Forum, Salt Rock Hotel,
4-5 May 2010

Status on the Development and Implementation of PBS Heavy Vehicles


Paul Nordengen
Research Group Leader: Network Asset
Management Systems
CSIR Built Environment




KEY ELEMENTS IN HEAVY VEHICLE ROAD TRANSPORT

- Road infrastructure
- Vehicles (design, maintenance & operation)
- Drivers

Prescriptive vs Performance-based Standards



- What the vehicle looks like




- What the vehicle can do






Low-Speed Offtracking




from NTC/Austrroads PBS National Workshops

Maximum Width of Swept Path



from Ervin and Guy (1986)

Static Rollover Threshold (SRT)



from NTC/Austrroads PBS National Workshops

Rollover in a steady turn





**ABNORMAL LENGTH
VEHICLE - 27m**

EDY204QP

AFRIT
QUALITY ON TIME

AFRIT
QUALITY ON TIME

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT

AFRIT





ABNORMAL LENGTH VEHICLE - 27M

Timber24

NP 22147

RTMS


62

ACTROS V6

PBS Lane Change Manoeuvre (SAE J2179)

Course and test specifications:

- 2.5 second period
- 24.5 m/sec (55mph)
- 61 m (200 ft) maneuvering section
- 1.46 m (4.8 ft) lateral displacement
- 0.15 g peak lateral acceleration



* not drawn to scale

Baseline cf. PBS vehicle





baseline

Last_Run Time= 2.4000 Frame=50



PBS

Last_Run Time= 2.4000 Frame=50





ABNORMAL LENGTH VEHICLE 24m

NP 157-944

RTMS

ACTROS

V6

super group

super group

LOADTECH

ERB

CAT




super group
ABNORMAL LENGTH VEHICLE 24m



MH 157-944




Mondi PBS Vehicle Route




Fuel Usage Comparisons


LITRES FUEL USED PER 400,000 TONNES @ 171 KM LEAD DISTANCE



Fuel Consumption




Fuel Efficiency




Parameters to Monitor

- Routes travelled
- Distance travelled per month and lead distance per trip
- Combination mass and payload
- Average speeds (loaded & unloaded)
- Trip duration
- Fuel consumption & efficiency
- Incidents/accidents, Breakdowns
- Tyre life and costs
- Life cycle of foundation brakes, Suspension life
- Community reaction


Payload and Combination Mass per trip



Average Payload



Payload Efficiency Factor (PEF)



OECD Project: Moving Freight with Better Trucks




LIST OF TRUCKS PROPOSED BY MEMBERS OF THE WORKING GROUP

Country	Description	Axle	length	Max weight		
Australia 1	Australian B Double Tractor + 2 trailers	9	26	68		
Australia 2	Australian B-Triple Tractor + 3 trailers	12	35 or 36.5	90.5		
Australia 3	Australian semi trailer	6	19	45.5		
Belgium 1 (same as Germany 1? And Denmark 1)	Tractor trailer	+	5	15.5 – 16.5 m	44 t in Belgium 40 t in EU	
Belgium 2 (same as France 1?)	Tractor trailer	+	4	15.5 – 16.5 m	39 t in Belgium 38 t in EU	
Belgium 3 (same as Denmark 5)	Tractor trailers	+ 2	8	25.25	60 t	
Canada 1	Tractor trailer	+	5	23 (max)	39.5	
Canada 2	Tractor Trailer	+	6	23 (max)	46.5	
Canada 3	Tractor trailers	+ 2	8	25 (max)	62.5	
Canada 4	Tractor trailers	+2	8 or 9	40 to 42 m	62.5	
Denmark 1	Tractor trailer,	+	5	16.5	40	

OECD Project: Moving Freight with Better Trucks




Payload Efficiency Factor - country













OECD Project: Moving Freight with Better Trucks




Payload Efficiency Factor - vehicles




Comparison of Baseline and PBS vehicles on Road Wear: Input data



Road Wear Effects



Road Wear Effects



Summary of Performance Outcomes

Two vehicles, 8 months operation

Performance indicator	Measured result
Payload	Average improvement: 19.3 %
Payload Efficiency Factor	Increase from 69.3 % to 70.5 %
Tons transported per month	Average increase: 19.3 %
Fuel consumption	Average savings: 12.7 %
Fuel savings (based on 700 000 tons/annum contract)	485 000 litres per annum
Fleet size	Reduction of 17 %
Incident/accidents*	Reduction from 3.1 to 1.1 per month
CO ₂ emissions (based on 700 000 tons/annum contract)	Reduction of 1 280 tons of CO ₂ per annum
Road wear	Reduction varies from 2 to 23 %

* Based on a fleet of 45 new vehicle combinations incorporating a number of PBS design features

Way Forward

- KZN DoT approved 30 additional permits in Feb 2009
- 15 additional PBS vehicles commissioned by Dec 2009
- Others are in the design phase
- Other PBS demonstration projects in the concept/design phase:
 - ◆ General freight (vehicle parts)
 - ◆ Mining
 - ◆ Steel pipes
 - ◆ Sugar
 - ◆ Car carriers
- Route classification
- Manage negative publicity from rail lobbyists and others

OECD Project: Moving Freight with Better Trucks




Figure 21: Low speed swept path performance by region

OECD Project: Moving Freight with Better Trucks




Figure 24: Static rollover threshold performance by region

Thank you for your
attention

