

cncPAVE Update

Bryan Perrie
The Concrete Institute



Developments

- **cncPAVE has been transferred to**
 - **The Concrete Institute (TCI)**
- **TCI responsible for the:**
 - **distribution of the cncPAVE program,**
 - **technical assistance in using the program,**
 - **future development,**
 - **calibration,**
 - **updating**

cncPAVE



- **Annual cost per user is R10 000 (excl. VAT)**
- **Cost includes:**
 - **Technical support (Dr Pieter Strauss)**
 - **IT support (Jaco Pretorius)**
 - **A free one-day course on the use of the program**
 - **Course venue in Gauteng**
 - **Other venues dependent on demand**

cncPAVE



- **The latest cncPAVE program is a web-based**
- **Access system from anywhere by using a compatible Internet Browser like:**
 - Microsoft Internet Explorer or Mozilla Firefox.
 - Recommend Mozilla Firefox
- **Single user licence – One per company (Username/Password)**
- **A full presentation and demo will be given at the November RPF.**

cncPAVE


- **Processing and loading will be slower than a locally installed application, but;**
- **Comparing cncPAVE to its old version,**
 - Always working with latest software
 - Data is always stored.
 - Accessing the data at any time from any location is a huge advantage.
 - Data is also stored per Company, Project and then Scenario, which makes data organizing a pleasure.


cncPAVE









- Look and feel the same as old version

Home | [Change Password](#) | [Sign Out](#)


Royal HaskoningDHV
Enhancing Society Together
William Jones: License expires on 08/05/2016

 **cncPAVE**
6.0.0.0




Main Page 





Control | Axle Loads | Facts | Distributions | Build-ups | What-if

Years to 1st Rehabilitation: 

Variables | Constants

 Save  Cancel  Export

Variables					
No.	Description	Min	Q	Best	Max
1	Cement content (kg/m ³)	0.9		440	1.1
2	Water content (l/m ³)	0.8		150	1.5
3	Flexural strength (MPa)	0.75		11	1.6
4	Layer 1 (slab) H1 (mm)	0.95		55	1.1
5	Layer 2 (subb) E2 (MPa)	0.67		1200	1.5
6	Layer 2 (subb) H2 (mm)	0.85		125	1.2
7	Layer 3 E3 (MPa)	0.8		150	1.3
8	Layer 3 H3 (mm)	0.8		150	1.3
9	Layer 4 E4 (MPa)	0.8		120	1.3
10	Layer 4 H4 (mm)	0.8		150	1.3
11	Layer 5 E5 (MPa)	0.6		80	2
12	Growth of HV traffic (%PA)	0.85		3.5	1.15
13	Speed of HV (Avg km/h)	0.2		60	2
14	Contact Pressure (MPa)	0.5		0.6	2
15	Annual Rainfall (mm PA)	0.7		760	1.3





- Projects
- Default (08/05/2015)
 - Default Scenario 1 (Jointed)
 - Default Scenario 2 (Dowelled)
 - Default Scenario 3 (Continuously Reinforced)
 - Default Scenario 4 (Ultra-Thin Continuously Reinforced)

Years to 1st Rehabilitation:

Variables Constants

Save Cancel Export

Variables				
No.	Description	Min Q	Best	Max
1	Cement content (kg/m ³)	0.9	340	1.1
2	Water content (l/m ³)	0.8	170	1.5
3	Flexural strength (MPa)	0.75	4.2	1.6
4	Layer 1 (slab) H1 (mm)	0.95	185	1.1
5	Layer 2 (subb) E2 (MPa)	0.67	1200	1.5
6	Layer 2 (subb) H2 (mm)	0.85	125	1.2
7	Layer 3 E3 (MPa)	0.8	150	1.3
8	Layer 3 H3 (mm)	0.8	150	1.3
9	Layer 4 E4 (MPa)	0.8	120	1.3
10	Layer 4 H4 (mm)	0.8	150	1.3
11	Layer 5 E5 (MPa)	0.6	80	2
12	Growth of HV traffic (%PA)	0.85	3.5	1.15
13	Speed of HV (Avg km/h)	0.2	60	2
14	Contact Pressure (MPa)	0.5	0.6	2
15	Annual Rainfall (mm PA)	0.7	760	1.3
16	Daily Temperature Cycle (°C)	0.6	18	1.5
17	Joint Movement (mm)	0.1	0	2.5
18	Void extra Vex (m)	0.01	0	2
19	Initial IRI (m/km)	0.7	1.5	1.5

Save Cancel [Input Guide](#)






Traffic Situation : T2: %LongHV 35-55; Weak LE

Linear
 Exponential
 K-Factor:

Projects

- Default (08/05/2015)
 - Default Scenario 1 (Jointed)
 - Default Scenario 2 (Dowelled)
 - Default Scenario 3 (Continuously Reinforced)
 - Default Scenario 4 (Ultra-Thin Continuously Reinforced)

Load (t)	Frequency (%)
0.5	1.270
1.5	11.460
2.5	19.320
3.5	13.500
4.5	10.630
5.5	9.480
6.5	6.560
7.5	5.660
8.5	7.450
9.5	7.050
10.5	4.610
11.5	2.040
12.5	0.700
13.5	0.210
14.5	0.060
15.5	0.000
16.5	0.000
17.5	0.000
18.5	0.000
19.5	0.000
20.5	0.000



Main Page



Control

Axle Loads

Facts

Distributions

Build-ups

What-if

 Export to Excel

Typical Rehabilitation Schedule				
Round	Step	Year	pwr	PWR
1	20.00	20.00	13.30	13.30
2	13.90	33.90	3.72	17.02
	(11.33	45.23)		


 Export to Excel





No.	Variable	Average	Std. Dev.
1	Crack width (mm)	1.15	0.08
2	Relative movement (mm)	0.09	0.00
3	Stiffness Ee (MPa)	102.02	18.77
4	Stress Sts (MPa)	0.47	0.06
5	HV axles n (million)	62.74	1.01
6	Total E80 (million)	38.89	0.62
7	Curl (m)	0.17	0.07
8	Deflection (mm)	0.07	0.01
9	Crack space X (m)	1.33	0.20
10	Void (m)	0.25	0.08
11	Shattered SH (%)	0.39	0.27
12	Pumping PU (%)	0.01	0.01
13	Faulting FA (%)	0.00	0.00
14	Construction Cost (per m ²)	642.04	11.51
15	PW Rehab (per m ²)	17.33	3.62
16	Life cost (per m ²)	659.37	11.51
17	IRI (m/km)	1.61	0.25


Projects

Default (08/05/2015)

 Default Scenario 1 (Jointed)

 Default Scenario 2 (Dowelled)


 Default Scenario 3 (Continuously Reinforced)

 Default Scenario 4 (Ultra-Thin Continuously Reinforced)



- Projects
- Default (08/05/2015)
 - Default Scenario 1 (Jointed)
 - Default Scenario 2 (Dowelled)
 - Default Scenario 3 (Continuously Reinforced)**
 - Default Scenario 4 (Ultra-Thin Continuously Reinforced)

Chart to print:



Main Page



Projects

Default (08/05/2015)

Default Scenario 1 (Jointed)

Default Scenario 2 (Dowelled)

Default Scenario 3 (Continuously Reinforced)

Default Scenario 4 (Ultra-Thin Continuously Reinforced)

Control

Axle Loads

Facts

Distributions

Build-ups

What-if



Input Value:

4.2

21-Point Range Width:

Zero

±10%

±20%

Variability:


Yes

No



Input to test: 3. Flexural strength (MPa)

Output to watch: 11. Shattered SH (%)





- Introduction
 - System Use
 - Rationale
 - History
 - Support
- The Sign-in Window
- Using cncPAVE
 - Important Notes
 - A Summary of the Interface**
 - Changing my Password
 - Creating Projects and Scenarios
 - Control
 - Axle Loads
 - Facts
 - Distributions
 - Build-ups
 - What-If
- General Concepts
- Pavement Concepts
- Traffic Concepts
- Statistical Concepts
- Economic Concepts
- Literature

Navigation: Using cncPAVE >

A Summary of the Interface

Once signed into the system, a window as illustrated below will appear:

1 - Systellence logo
 2 - User name: Jaco Pretorius
 3 - License expiry: 01-10-2015
 4 - Control tab
 5 - Axle Loads sub-tab
 6 - Facts sub-tab
 7 - Distributions sub-tab
 8 - Build-ups sub-tab
 9 - What-if sub-tab
 10 - Home | Change Password | Sign Out links
 11 - cncPAVE 6.0.0.0 version information
 12 - Help icon
 13 - Projects and Scenarios section
 14 - Projects list

Variables				
No.	Description	Min Q	Best	Max
1	Cement content (kg/m ³)	0.9	340	1.1
2	Water content (l/m ³)	0.9	170	1.3
3	Flexural strength (MPa)	0.75	4.2	1.6
4	Layer 1 (slab) H1 (mm)	0.95	240	1.1
5	Layer 2 (subb) E2 (MPa)	0.67	1200	1.5
6	Layer 2 (subb) H2 (mm)	0.85	125	1.2
7	Layer 3 E3 (MPa)	0.8	150	1.3
8	Layer 3 H3 (mm)	0.8	150	1.3

Below, all points are discussed. The idea of this discussion is just to give an overview of the Main Interface of cncPAVE. A more detailed discussion on each section will follow later within this Help facility.

- 1 - At this point, your Company's logo will be displayed.
- 2 - The name of your Company will appear at this point.
- 3 - User and Subscription details. At this point, your name, surname and the expiry date of your subscription will be displayed.
- 4 - **Control**: By clicking the page button at this point, you will view and configure all properties under Control. The system is divided into different sections by making use of a Page Control as illustrated.
- 5 - **Axle Loads**: All the Traffic Situation Values can be configured by clicking the page button at this point.
- 6 - After running calculations as discussed later, **Facts** and a Typical Rehabilitation Schedule will be available at this point.
- 7 - **Distribution**: Graphs will be available after running calculations as discussed later. By clicking the Page Button at this point these graphs can be viewed and exported.
- 8 - **Build-up**: Graphs will be available after running calculations as discussed later. By clicking the Page Button at this point these graphs can be viewed and exported.
- 9 - By accessing this section, **What-If** analysis can be done.
- 10 - To **change your password**, click the link at this location.
- 11 - To sign out of cncPAVE, click the link at this location. As discussed before, **it is very important to sign out** before closing the Internet Browser.
- 12 - cncPAVE's version information is displayed at this point.
- 13 - To access this Help facility, simply click the button at this point.
- 14 - **Projects and Scenarios** section. Within this section, Projects and Scenarios are listed. This will be discussed in more detail.

cncPAVE

- For more information
- www.theconcreteinstitute.org.za
- Contact Loré de Bernier 011 315 0300 or loredb@theconcreteinstitute.org.za
- Details will shortly be available on the TCI website: www.theconcreteinstitute.org.za

Developments

