



Sanral Field testing: R35 Data and R104 Trial Sections

Wynand JvdM Steyn
University of Pretoria

- Field testing background
- Provisional R35 data
- R104 planning



Field testing background

- Objective:
 - Benchmark of pavement material parameters (σ , ϵ , δ)
 - Not calibration
- Place in Sanral project
 - After materials model developments
- Expected outcome
 - Verification of parameters predicted using materials models

Provisional R35 data

- R35 used to evaluate selected instruments
- Evaluate installation procedure and data collection process



Site instrumentation

- R35

Pressure cells (V and H), Strain gauges,
Accelerometers, Pressure film





Horizontal and vertical pressure under roller





Horizontal and vertical pressure under roller



Parameter	Loose condition	Compacted condition
Maximum vertical pressure [kPa]	214.0	282.9
Maximum horizontal pressure [kPa]	6.4	4.1
Vertical pressure : Horizontal pressure ratio	33.5	69.6

Horizontal and vertical pressure under roller


- Working with reasonable values
- Appear robust for longer term measurements
- Appreciate that presence of sensors will affect stresses – need to measure somewhere



Accelerometer data




10:35 - loose




Ax Ay Az


11:50 - compacted



Ax Ay Az





Ax Ay Az



Ax Ay Az

Strain under roller



Strain under roller





- Working well with reasonable data
- Appears robust



Pressure film under roller



Pressure film under roller




Pressure film under roller

- Reasonable values
- Care regarding protection of handles
- Appear robust
- High temperature option available



Emu Coils

- Measuring strain / displacement
- Long history in UK, New Zealand
- Organized in stacks to measure horizontal, vertical and longitudinal movement



R104 planning


- Planning process
- Location
- Test sections
- Instruments




Planning process

- Submission of designs
- Input regarding sensors requirements
- Collation of designs and plans
- Budget
- Start construction

Location



Location



<p>Project Name: N4 Upgrade from Bronkhorstspuit to Diamond Hill</p> <p>Client: National Road Agency</p> <p>Contract No: N4-UPG-01</p> <p>Scale: 1:1000</p>		<p>SS1</p> <p>SA 1000</p> <p>SA 1000</p>	<p>P.O. Box 9000</p> <p>Midrand 1685</p> <p>Tel: 011-707 9000</p> <p>Fax: 011-707 9000</p>	<p>DATE: 2011-01-10</p> <p>BY: [Signature]</p> <p>FOR: [Signature]</p>	<p>PROJECT NUMBER: SA 1000/01/0001/1/1</p> <p>PROJECT NAME: N4 Upgrade from Bronkhorstspuit to Diamond Hill</p> <p>SCALE: 1:1000</p>
-------------------------------------------------------------------------------------------------------------------------------------------------------------	--	------------------------------------------	--------------------------------------------------------------------------------------------	------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------

Location

- R104 Bronkhorstspuit
- 10 pavement types (21 sections)
- Between 16 m and 100 m long
- 2 lanes
 - 1 instrumented (outer)
 - 1 duplicate – normal traffic




Test sections

- Natural gravel base
- Inverted G1
- Foam Treated Base (FTB)
- Emulsion Treated Base (ETB)
- Cement Treated Base (CTB)
- Bitumen-based (HiMA)
- Bitumen-based (BTB)
- Jointed Concrete
- Ultra-Thin Continuously Reinforced Concrete Pavement (UTCRCPC)
- Block paving

Test sections

- At least 1.32 MESA
- Layout allows for
80 km/h truck speeds over sections
- Subgrade and subbase
Similar subgrade for all sections
Subbase
 - C4 – all except below
 - G5 / G7 – G4, FTB, ETB, CTB, JC1

Typical Test sections - Granular



Sensors

- Initial shopping list
- Primary and secondary sensors
- Costs
- Order lead times
- Sensor clusters per section
- Final list of sensors

What is required to benchmark data

Sensors - Initial shopping list

- 41 Pressure cells
- 42 Strain gauges
- 47 Pressure films
- 10 Accelerometers
- 14 Moisture sensors
- 80 Temperature sensors
- 7 Strain gauges on steel
- 8 MDDs
- 121 ϵ mu coils
- 36 JDMDs
- 1 Weather station

Progress

- Currently preparation of subgrade layer
- Expected to start with construction late in November 2012
- Measurements only after all construction has been completed

