

APPLICATION OF A NEW UTCRCP DESIGN ON THE N1/1

Philip Joubert (RHDHV)

29th Road Pavements Forum

12 May 2015

CONTENTS


- **Project Information and Background**
- **UTCRCRP Performance**
- **Contributing Factors**
- **New UTCRCRP Design**
- **FEM Design Review**

PROJECT INFORMATION

- **Appointment:**
 - **RHDHV by SANRAL to undertake remedial measures on the pavement of the Truck Crawler Lane (UTCRCP)**

- **Location:**
 - **Huguenot Toll Plaza to Huguenot Tunnel West Portal**

PROJECT LOCATION



PROJECT BACKGROUND

ORIGINAL CONSTRUCTION (*R Burger RPF 2010*):

- 2009 - N1/1 Rehabilitation / Widening (Martin & East)
- Truck crawler lane as an experimental UTCRCP section



LAYOUT: TRUCK CRAWLER LANE



PROJECT BACKGROUND

UTCRCRP: Ultra Thin Continuous Reinforced Concrete Pavement



- **50 mm thick concrete pavement**
- **Concrete strength:**
 - **90 MPa minimum Compressive (cubes)**
 - **10 MPa minimum Flexural (beams)**
- **5.6 mm mesh (50 x 100 mm) – approximately 6% steel**
- **100 kg steel fibre per m³**
- **Polypropylene fibre (2 kg)**
- **Intermediate beams at $\pm 300\text{m}$**

PROJECT BACKGROUND

UTCRCRP: (17 500m²)



PROJECT BACKGROUND



PROJECT BACKGROUND



PROJECT BACKGROUND

UTCRCRP: Ultra Thin Continuous Reinforced Concrete Pavement



UTCRC P PERFORMANCE

UTCRCRP PERFORMANCE (Good Section)



UTCRCRP PERFORMANCE (Blow Up)



UTCRCPC PERFORMANCE (Movement)



UTCRCRP PERFORMANCE (Transverse Joints)



Van Zyl

Page 16

UTCRCRP PERFORMANCE (Movement)



UTCRCRP PERFORMANCE (Transverse Mesh Cracking)



Mbongwa

Page 18

UTCRCRP PERFORMANCE (Block Mesh Cracking)



van Zyl

Page 19

UTCRCRP PERFORMANCE (Joint opening)



Mbongwa

Page 20

UTCRCRP PERFORMANCE (Transverse Joint Spalling)




UTCRCRP PERFORMANCE (Pumping of Fines)



CONTRIBUTING FACTORS

CONTRIBUTING FACTORS

- **Warping**



(b) Night (slab bottom temp > surface temp)

Mbongwa

CONTRIBUTING FACTORS

- **Moisture Ingress**



CONTRIBUTING FACTORS

. Thermal Expansion

- Coefficient: $12.9 \times 10^{-6}/^{\circ}\text{C}$
- Typical day joints: 50 – 60m
- For temperature change:
 - from 20 to 50°C
 - 23mm movement



CONTRIBUTING FACTORS

. Traffic Loading Downhill Force




CONTRIBUTING FACTORS

. Delamination



REMEDIAL ACTIONS : CRAWLER LANE



NEW UTCRCP DESIGN

- **Design Objective:**
 - **Address issues identified on the N1/1**
- **R104 Experimental Section:**
 - **Aspects of the design implemented**

NEW UTCRCP DESIGN

- **Buckling / Warping / Construction:**
 - **Thickness 70mm (100mm)**
 - **Longitudinal edge beams (150 x 300)**
 - **Lower concrete strength (FS > 7.5MPa)**
 - **Reduction in % reinforcing**

NEW UTCRCP DESIGN

- **Strengthen day joints:**
 - **Thickened slab**
 - **Tie bars**
 - **Key joints**

NEW UTCRCP DESIGN

- **Movement:**
 - **Intermediate beams @ day joints (60m)**
 - **Improved longitudinal joint seals**

FINITE ELEMENT METHOD (FEM)

UTCRCRCP DESIGN REVIEW

UTCRCRP FEM DESIGN REVIEW


Material Characterization:

- **Support layers**
 - **Subbase**
 - **Subgrade**

- **New UTCRCRP**
 - **Universities Pretoria – Mix design**
 - **University of Stellenbosch – Expansion coefficients**


UTCRC FEM DESIGN REVIEW

Disk Test: TM 35 GPa, UCS 50 MPa, UTS 8 MPa, ν 1.5E-3
Time = 0




UTCRC FEM DESIGN REVIEW

Disk Test: TM 35 GPa, UCS 50 MPa, UTS 8 MPa, ϵ_c 1.5E-3
Time = 0.25
Number of elements cracked=166



UTCRC FEM DESIGN REVIEW



UTCRCRP FEM DESIGN REVIEW

- **FEM Analysis:**
 - **Model selection and compilation**
 - **Model calibration**
 - **Existing UTCRCRP Pavement**
 - **New UTCRCRP**
- **Report and Recommendations**

CONSTRUCTION COMMENCE

SEPTEMBER 2015

Acknowledgements:

Riaan Burger – SANRAL

Pieter Molenaar – RHDHV

Pieter van Vreden – RHDHV

Dr Pieter Strauss

Gerrie van Zyl – Mycube AMS

Leon Mbongwa